


Installation and operating instructions

Spaceguard Belt Conveyor

Safety note: Spaceguard conveyors are designed for incorporation, therefore a relevant risk assessment and safe working method, must be carried out by the customer prior to use. This manual contains important safety information regarding your conveyor



Additional support sheets maybe available for your individual product. These are attached to the pallet the conveyors were shipped on.

Conveyor Training

Prior to the use of automation equipment, Spaceguard Recommends the following courses which is available through various recognised health and safety course providers.

IOSH Working safely: 1 day (aimed at all employees)

To enable individuals to reduce the risk of accidents and incidents at work.

To help them apply sound-working principles of Health & Safety effectively.

To enable trainees to demonstrate their competencies in successfully completing a practical & written exam, to the performance criteria specified by IOSH.

Content: Health & Safety at Work, Hazards & Risks, Common Hazards at Work, Risk & Risk control,

Positive Safety Behaviour, Safe System at Work, Common Hazards

IOSH Managing safely: 5 days (aimed at managers) (Also available as an online course)

To enable delegates to apply sound health and safety principles to the management of health and safety at work.

To enable delegates to become competent and demonstrate this by successfully completing a practical and written exam to the performance criteria specified by IOSH.

To build up an in-depth awareness of health and safety practices, its implementation and the legal aspects and how to apply it in their workplace.

To understand health and safety risk, its assessment and the use of accident investigation and prevention.

Additional Training

We would always recommend application specific training for your staff prior to using any conveyor or automation item. This would normally also include manual handling techniques and use of PPE. When using, loading and unloading conveyors correct manual handling techniques should be used. We would also recommend as part of your training, you highlight any areas of residual risk, (and add additional guarding if required) and ensure they do not go underneath a moving conveyor, or enters areas of residual risk.

Assembly and installation

The conveyor is supplied part pre assembled - if 3m or under or part assembled if over 3m, conveyor assembly is to be completed by the customers appointed competent team, using safe methods and required equipment at the customers site.



WARNING

Risk of injuries due to incorrect assembly & installation

- A risk assessment, method statement & safe working / installation procedures must be carried out prior to site and installation.
- Conveyor assembly and installation must be carried out by trained, competent and qualified personnel in accordance with the relevant safety standards.
- When erecting conveyor systems, safe systems of work, competent people and adequate lifting aids (machines) (all lifting aids must be only used within the manufacturers limits) must be used. (additional lifting eyes maybe required on the conveyor dependent on the application.) (customer may need to put holes in the bed to accommodate these.)

General installation safety

- Carry out risk assessment and devise a safe working procedure.
- Check conveyor structure to ensure you can safely install.
- Ensure work area is clear of obstruction and you have the room available to safely install.
- Cordon off the work area to prevent access by non authorised personnel
- Use lifting aids to minimise manual handling. (ensure your installer is trained, qualified and competent to use the lifting aids safely.
- Ensure lifting aids are suitable for the installation and are tested, checked and deemed safe.
- Spaceguard recommends the use of best practice work equipment. Example if possible use a tested / correctly installed work platform rather than a ladder. (If using ladders and steps - these must be suitable for the task, tagged and checked prior to use.)

Assembly and installation

- Using best practices, safely lifting one section at a time, bolt and tighten the legs to the conveyor. On large structures ensure each section is fully braced prior to adding next section. (ensure prior to adding the second section onwards the conveyor is in its final place. (secure 1st leg.)
- When adding section ensure the conveyor is straight. (use plumb line)
- When all sections are in place, check and ensure all conveyor fixings have been tightened.
- Set the conveyor to the required height using the adjustable feet and use the locking nuts to secure them - Use a spirit level for this task
- If using adjustable feet, secure the conveyor to the ground and additional structures, with the relevant fixing kit, ensuring the frames are not warped.
- When aligning the conveyor ensure, ensure there is no contact between moving parts.



WARNING

Risk of injuries due to incorrect assembly

- A risk assessment, method statement & SWP* must be carried out prior to final assembly and installation.
- Assembly must be carried out by competent and qualified personnel in accordance with the relevant safety instructions.
- Carefully assembly all connections, eg cables, hoses and pipes and check they are corrected correctly

* SWP (Safe working procedure)

- Pay attention to the tracking of the belt - (Refer to tracking page)
- After conveyor installation, make sure passageways are clear. If conveyors are to be crossed, put in walkways
- When integrating conveyor into a system or a process, a risk assessment must be carried out for the conveyor to reach conformity, Always consider possible danger zones including areas where crushing and cuts can occur.
- PPE and Safe working practices should also be adopted

Electrical Installation

DANGER



Danger of death due to live cable ends!

- Electrical installation should only be carried out by experienced / qualified / competent electrical personnel
- Disconnect from power supply
- Observe the minimum bending and wear

- Power is to be supplied to the conveyor by relevant isolated plug or direct into a control panel through an isolator
- Always check cable for damage
- Connect motor in accordance with EN-IEC 60204-1 - refer to motor wiring pages for wiring information

Start up and operation

Initial Start up - *To be carried out by competent persons*

WARNING



Risk of injuries due to incorrect installation

- Check risk assessment and method statement have been carried out.
 - Check all aspects of installation. Ensure correctly installed
 - Check electrical connections and protective equipment
 - Ensure all unauthorised / untrained personnel are removed from the area, Wear appropriate PPE
-
- Check direction of travel prior to initial start up. If required correct the direction. (optimum performance is achieved with the drive pulling the belt.)
 - Check the belt tracking and adjust if required. (see belt tracking support)

Operation

Prior to each operation

- Check the conveyor for signs of visual damage. Pay special attention to belts, support stands and wiring
- Ensure that all safety equipment is functioning properly
- Make sure only authorised and trained personnel are in the conveyor work area and they are wearing all the appropriate PPE.
- Ensure the work area is clear from obstruction and is tidy
- Provide instructions and monitor, loading and unloading the conveyor

WARNING



Rotating parts!

Crushing and serious injury due to being caught and pulled into the conveyor

- Do not remove any guarding
 - Never wear loose clothes and tie long hair back
 - Keep hands and body parts away from moving parts
 - Follow safe working practice when using conveyors
-
- **If goods become trapped within the conveyor, do not just pull the object, Isolate the conveyor and find out why and how the jam has occurred**

Procedure for accidents or malfunctioning

- Stop the conveyor and isolate
- Accident - Apply first aid and call emergency services
- Inform a specialist (A specialist must eliminate the fault)
- Only restart after the conveyor has been deemed safe by a specialist

Disposal

- Adhere to the manufacturers disposal documents when disposing of oil, recycle parts if possible.

Environmental - considerations

- Turn off the power to the conveyor when not in use
- Ensure waste oils, belts etc are disposed of in accordance to regulations

Conveyor Safety

Basic Safety instructions



The conveyor was generally safe to operate at time of delivery, however dangers may still arise during use. A safe working practice, risk assessments must be carried out by the user covering all aspects of use within the incorporated system, process or machine. All staff to be properly trained in all aspects.

- Danger of personal injury or death for operators and others
- Adverse effects on the conveyor and other items

Non adherence to the information in these instructions and information within this manual can result in life threatening injury.

Intended use

This design belt conveyor are intended for incorporation in a wide range of industrial systems, machines and food environments to transport goods. All conveyors are built to suit the application information the direct customer or reseller has provided. They are not recommended for use outside of these parameters without further assessment by the manufacturer.

Do not exceed the conveyor limits, if unsure contact your conveyor supplier prior to use.

Incorrect Use

The conveyor is not intended at any time, under any situation, to transport, people and some transportation of hazardous chemicals, please check with you supplier

Specialists

Specialists are people who have knowledge of conveyor items and understand the instructions, and have the ability to carry out work professionally whilst knowing and observing regulations.

Competent Person

A person is regarded as competent if they have 'sufficient training and experience or knowledge and other qualities to properly and safely carry out the required operation ' without causing risk to themselves or others'.

Electricians

Electricians must be able to assess and recognise possible dangers when performing tasks, due to training, experience and knowledge of regulations.

Motor wiring diagrams are contained within this manual.

Conveyor Safety

Dangers



The following dangers are some of the various dangers which may occur when operating, maintaining or cleaning the conveyor.

Spaceguard recommends staff to be trained, conveyor to be maintained in accordance to these instructions and conveyor to be checked daily prior to use

Safety Equipment

- Only carry out maintenance when the conveyor is switched off and measures taken so it cannot be started
- Organise additional measures to restrict access to the conveyor
- Never remove any guarding whilst the machine is running.
- Regularly inspect safety equipment and barriers
- Always wear PPE that is in good condition

Electricity

- Never reach into a live machine - Always Isolate from supply

Rotating parts

- Never wear loose clothing
- Never wear jewelry
- If long hair - wear a hair net

Work environment

- Keep work area tidy and clear of obstruction
- Wear safety shoes + other site minimum PPE including gloves
- Monitor work practice

Malfunctioning

- Inspect the conveyor for damage
- Be aware of any smoke or unusual noises, (Isolate at mains and seek advise)
- Clean up any oil spills
- Do not climb on the conveyor
- If Objects get jammed - Do not just pull - Isolated the conveyor and find cause of jam

Maintenance - Isolate prior to maintenance

- Carry out maintenance regularly
- Only use original spare parts

Incorporation

Danger zones can arise when integrating the conveyor into a system, machine or process. These danger zones are not covered in these instructions. These must be analysed during final assembly and installation and first start up. *Safe working practices and relevant training should be given to personnel.*

If necessary, implement and add further constructional methods

Conveyor Safety

PPE



Spaceguard recommends staff to be trained, and well maintained PPE worn as appropriate. PPE should be checked daily prior to use.

SAFETY SHOES



Spaceguard recommends all staff working around conveyor equipment to wear safety shoes. Specific type should depend on application, please take suitable advise from health and safety consultants.



TYPE OF SIGN TO BE DISPLAYED

Conveyor Safety

PPE



Spaceguard recommends staff to be trained, and well maintained PPE worn as appropriate. PPE should be checked daily prior to use.

NOISE

The level at which employers must provide hearing protection and hearing protection zones is now 85 decibels (daily or weekly average exposure) and the level at which employers must assess the risk to workers' health and provide them with information and training is now 80 decibels. There is also an exposure limit value of 87 decibels, taking account of any reduction in exposure provided by hearing protection, above which workers must not be exposed. From HSE website

Ear protection options



Headband comfort ear defenders

For reduction of upto 30db

Foam disposable ear plugs




For reduction of upto 25db

Banded ear plugs



For reduction of upto 20db



TYPE OF SIGN TO BE DISPLAYED

Conveyor Safety

PPE



Spaceguard recommends staff to be trained, and well maintained PPE worn as appropriate. PPE should be checked daily prior to use.

Ensure long hair is tied up.

LOOSE HAIR



Spaceguard recommends all staff working around conveyor equipment to wear hair nets or appropriate means to tie long hair up and out of the way. Specific type should depend on application, please take suitable advice from health and safety consultants.



TYPE OF SIGN TO BE DISPLAYED

Conveyor Safety

PPE



Spaceguard recommends staff to be trained, and well maintained PPE worn as appropriate. PPE should be checked daily prior to use.

EYE Protection

Safety Glasses with impact lenses.



A suitable pair for task should be used. Spaceguard recommends. Advise should be taken from a health and safety consultant.

Safety Goggles with impact lenses.



A suitable pair for task should be used. Spaceguard recommends. Advise should be taken from a health and safety consultant. More used with high speed particles

Full face visor with impact lenses.



A suitable pair for task should be used. Spaceguard recommends. Advise should be taken from a health and safety consultant. More used with high speed particles and liquid splashes.



TYPE OF SIGN TO BE DISPLAYED

Conveyor Safety

 <p>Do Not Climb, Sit, Stand, Walk, Ride, or Touch the Conveyor at Any Time</p>	 <p>Do Not Perform Maintenance on Conveyor Until Electrical, Air, Hydraulic and Gravity Energy Sources Have Been Locked Out and Blocked</p>	 <p>Operate Equipment Only With All Approved Covers and Guards in Place</p>
 <p>Do Not Load a Stopped Conveyor or Overload a Running Conveyor</p>	 <p>Ensure That All Personnel Are Clear of Equipment Before Starting</p>	 <p>Allow Only Authorized Personnel To Operate or Maintain Material Handling Equipment</p>
 <p>Do Not Modify or Misuse Conveyor Controls</p>	 <p>Keep Clothing, Body Parts and Hair Away from Conveyors</p>	 <p>Remove Trash, Paperwork and Other Debris Only When Power is Locked Out</p>
 <p>Ensure That ALL Controls and Pull Cords are Visible and Accessible</p>	 <p>Know the Location and Function of All Stop and Start Controls</p>	 <p>Report All Unsafe Conditions</p>

POST IN PROMINENT AREA

We recommend risk assessments and safe working practices are adopted prior to use.
Keep work areas clear

Noise

WARNING



- Conveyor noise level is not above 75db

Disposal

WARNING



- Conveyor should be disposed through normal channels.
- Note should be taken - Oil within motor
- Belt is PVC
- All other parts are normal metals and plastics

Transport, movement and storage

The conveyors will be delivered generally on a pallet, secured with strapping and heat shrunk, highlighted for incorporation. On the pallet, there will be the conveyor items, supports, fixings etc along with a incorporation paperwork and wiring detail.

Transport and movement

CAUTION



Risk of injuries due to incorrect transport

- Transport must be carried out by qualified and authorised personnel.
 - Lifting must be carried out by competent personnel
-
- Ensure people are not in danger - lift zone
 - Ensure pallet and conveyors are lifted and moved safely, we would recommend due to the size and nature of the items moved a specific risk assessment and safe working procedure should be carried out and adopted.
 - Wear appropriate PPE (including minimum Safety shoes and Gloves)

Delivery

- Prior to signing from the carrier the pallet must be inspected for damage. Notify the driver, by writing on their paperwork as damaged and contact your supplier. The carrier must be notified at time of delivery, to prevent any claims being refused.

Storage

WARNING



Risk of injuries due to incorrect Storage

- Do not stack conveyors on top of each other
- Do not place other objects on the conveyor
- Ensure conveyor is safely positioned prior to leaving it
- If the conveyor is not to be used straight away, protect from moisture and dust.

Movement - Conveyors supplied with castors

WARNING



Risk of injuries due to incorrect Movement - *if in doubt do not move*

- Ensure a risk assessment should also be carried out and a safe working procedure on regarding movement of conveyors
- Ensure the conveyor is free of objects prior to movement.
- Ensure the area is free from obstruction and floors swept.
- Ensure the castors are free to move without obstruction
- Ensure castors are in good condition.
- Ensure floor surface is suitable for moving conveyors
- Ensure the castors are locked prior to using the conveyor again.

Electrical Installation

DANGER



Danger of death due to live cable ends!

- Electrical installation should only be carried out by qualified / competent electrical personnel
 - Disconnect from power supply
 - Observe the minimum bending and wear
-
- Power is to be supplied to the panel by relevant isolated plug or direct into a control panel through an isolator
 - Always check cable for damage
 - Connect motor in accordance with EN-IEC 60204-1 - refer to motor wiring pages for wiring information

WARNING



Risk of injuries due to incorrect assembly

- A risk assessment and method statement must be carried out prior to final assembly and installation.
- Assembly must be carried out by competent and qualified personnel in accordance with the relevant safety instructions.
- Carefully assembly all connections, eg cables, hoses and pipes and check they are corrected correctly



Notice

Risk of injuries or death due to incorrect assembly

- Always ensure panels and electrical items are correctly earth bonded.
- Earth bonding and testing must be carried out by competent and qualified personnel in accordance with the relevant safety instructions, prior to putting this panel into service.

Standard Panel Wiring





Wiring diagram: Panel


Single drive. Start / Stop / Estop

Input Voltage : 1ph 240V




Output Voltage: 3ph 240V (Delta wiring)



Panel Connection



Customer Specific wiring - Customer to incorporate wiring



Remote Start - Customer wiring

Control panel inspection certificate

The manufacturer
Spaceguard Limited
Bergen Way, Hull, UK

Hereby declares that the control panel supplied

- Serial numbers between: 11000 - 19000

Is not a ready to use panel according to the EC machinery directive and therefore does not fully comply with the requirements of this directive.

Initial start up of these panels is not permitted until conformity of the entire machine / system / process in which they are installed has been declared via the EC machinery directive!

Insulation resistance test 1000V		
Control cables > 200MΩ	L1 to N > 200MΩ	N to PE > 200MΩ L1 to PE > 200MΩ

General


Panel wiring to BSEN 60204

All conveyor wiring to BS 7671 IEE regulations




Neil Ellerby
Director
29.08.2015


Geared Motor Wiring




1 Phase 230 V



1 Phase 230 V



3 Phase 400 V



3 Phase 230 V




Motor Rating Plate




Safety note: Always electrically test end earth bond conveyors prior to operation.

3-phase voltage—6 leads T.C




For counter clockwise rotation, change L2 and L3

3-phase voltage—6 or 9 leads T.C— dual voltage



1-phase voltage—7 leads T.C



Drum Motor Wiring

80S, 113S




All Spaceguard conveyors using drum motor which are also supplied with drum motor drives are also supplied with the drum motor manufacturers manual. This information is taken from the manufacturers manual.



Motor Rating Plate

Drum Motor : 80i, 113, & 135i

3-phase voltage delta/star connection



EMC

All applicable components within Spaceguard conveyors conform to the relevant EMC standards, A copy of the relevant certificates are held within our technical files. EMC testing should be carried out on the machine as a whole in its finished form by the customer.


Drum Motor Wiring

DM Series



Drum Motor : DM80, 113,135 & 165

3-phase voltage delta/star connection



Safety Data Sheets for belt materials

Storage

Keep in a neutral environment and do not expose products to direct sunlight.

Do not expose modules to extreme temperatures or open flame.
belts are flammable (does not apply to Flame

Installation

Use foot protection.
Use eye protection.
Use Gloves.

To avoid personal injury or damage to product, do not attempt to connect or disconnect conveyor modules unless you are familiar with conveyor module construction.

Before installing the chain or belt ensure that both the conveyor and belt are suitable for the application.

When connecting or disconnecting belt or chain:
Always lock out equipment power switch before removing or installing conveyor modules.

Use proper tools which should be in good condition.

Support the belt or chain to prevent uncontrolled movement.

Warnings

Fire

Modular plastic products are, unless clearly specified, made from materials which support open flame.
Products made from PVC & PU when so exposed, will emit toxic fumes.
Plastics should therefore not be exposed to extreme temperatures or open flame. Special care should be taken when undertaking repair work particularly when welding at a conveyor if the conveyor is fitted with plastic belts.

Personal Protection

Always use safety glasses when mounting or repairing chains and belts and while securing or removing pins.
Use only suitable tools in good condition.
The weight of some products calls for the use of safety shoes. When installing/removing or repairing belts on a conveyor, the motor must be turned off.



SPACEGUARD

Process and conveyor belting

Technical belt data sheet

Flexam EM 8/2 0+04 dark green AS FG



Article code 529106

General information

Product group	Synthetic belts
Market segment	Agriculture, Paper, General handling, Distribution centres
Main features	Foodgrade
Belt support	Slider bed, Rollers, Flat

Belt construction

Fabric tension layer	polyester	stable	2-ply
Topside	Flexam PVC	smooth	dark green
Bottomside	fabric	low friction	

Characteristics

Foodgrade (FG)	yes
Antistatic (AS)	yes
High conductive (HC)	no
Flame retardant (FR)	no
ATEX approval	no

Technical belt data

Hardness topside	according to DIN 53505	80A shore	
Force at 1% elongation	according to ISO 21181	8.0 N/mm	44.80 lbs./in.
Belt thickness	internal AB method KV.002	1.90 mm	0.075 in.
Weight	internal AB method KV.004	2.20 kg/m ²	0.451 lbs./ft. ²
Thickness top cover		0.40 mm	0.016 in.
Temperature range		-15 to 80 °C	5 to 176 °F
Temperature range short		-15 to 100 °C	5 to 212 °F
Min. pulley diameter flexing (A)		25.0 mm	0.984 in.
Min. pulley diameter back flexing (B)		50.0 mm	1.969 in.
Standard belt width		2000 mm	78.74 in.
Maximum belt width		3000 mm	118.11 in.

Endless instructions

Hot splicing is always preferable. Cold splicing can only be done when the belt is exposed to normal temperatures and the humidity is not excessive. For the working method, consult the splice information and the equipment literature. Apply the recommended splice as indicated in the separate information.

Additional information

The information applies at approx. 20°C (68°F). Keep the belt tension to a minimum for maximum belt and conveyor life. Stated is the belt temperature. The allowable product temperature may vary.

The diameters are valid for hot vulcanised splice and at the indicated belt force. Depending on the splice and working conditions (e.g. temperature), different pulley diameters may be possible or necessary. When fasteners are used the minimum diameters are increased by approx. 50%.

Consult our specialists for available profiles and accessories.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.

Conveyor Maintenance Schedule + Spares requirements

Conveyor maintenance, service and daily checks are an essential part of the reliable, safe running of any conveyor. Failure to carry out these simple checks, may have a detrimental effect on the conveyor and potential safety implications. Below is the outlined recommended checks and maintenance detail for belt conveyors.

CONVEYOR MUST BE ISOLATED PRIOR TO CARRYING OUT CHECKS & MAINTENANCE

Daily checks by trained nominated operator

- Check condition of conveyor for visual damage including belt, structure etc
- Check for obvious signs of wear or loose fixings
- Check for foreign bodies lodged on or in the belt conveyor
- Check condition of warning signs and operating procedure
- Check condition of electric buttons and knobs - (Do not open panels)
- Check all personal using have had relevant training **& have all required PPE**
- Check conveyor tracking is ok. (inform maintenance if this need adjusting)

If any problems or issues with the conveyor are found either during the prior to operation or during the working day. Stop using the conveyor, isolate and report to maintenance personnel and line managers.

Conveyor Maintenance - To be carried out by suitable qualified / competent person

- Check condition of belt
- Investigate Drive drum and return rollers for signs of wear.
- Check condition of external wiring.
- Tighten any loose fixings
- Grease any bearings as required
- Check and adjust tracking as required
- Check condition of warning signs and operating procedure
- Check condition of electric buttons and knobs
- Check panel wiring and carry out electrical tests on conveyor
- Look over conveyor body for signs of damage
- Check condition and functionality of guarding directly associated with the conveyor and conveyor process + report

Conveyor maintenance should be carried out on a regular basis by a competent person, Contact us to ascertain service interval for your product. Recommend service period should be between 3 and 12 months dependent on application. (the more arduous shorter service the interval. **FAILURE TO SERVICE CONVEYORS MAY CAUSE SAFETY RISKS.**

Spare parts

We would always recommend the stocking of spare parts which minimises down time on conveyors, in the event of a part failure.

Drum motor or geared motor (Normally 2 to 5 days)

Drive roller (Normally 1 week)

Drive bearings (Normally next day)

Idler roller (Normally 2 to 5 days)

Return roller (Normally 2 to 3 days)

Conveyor belt (Normally 2 to 3 days)

Costing and accurate delivery details, available on request

Conveyor Maintenance check list. Please fill out date and sign once work complete

[illegible]

Support sheet - Inclined conveyors

Prior to loading and use, thought must be given to where the conveyor is situated and the items you are putting on the conveyor, for example a shiny flat bottomed object will not go up inclined conveyors very well. Items with hot melt glue will not be suitable for PVC belt conveyors., or very long items will not go down incline conveyors very well. The position and work area around the conveyor should be clear of obstruction, *as it is often the location and the process which will limit functionality*


Before use

The rule of thumb is quite simple, unless you have had adequate training on the piece of equipment, do not use it. This training should include, safest use practices which is application dependent, if conveyor is to be loaded by hand, manual handling training etc. Once you have had the relevant safety training, ensure you familiarise yourself with the control function and process for your application. A driven conveyor by nature has moving parts and must be treated with care.

Ensure the work area is clear of obstruction and any personal within the work area are aware of the conveyor starting.

Loading and unloading manually

The recommendations are briefly as follows. Do not lift anything over 25 kg, the sketch below shows roughing what is and is not acceptable for male and female. If there is twisting or tight access involved these figures should be reduced by at least 20%.



Operational loading.


When working against the conveyor the rule of thumb is a maximum of 450mm reaching is acceptable. Please note the weights you can lift near your person are not the same as when you reach over something. - **NOMINAL OPTIMUM LOADING HEIGHT = 850mm**

Using incline conveyors with basic start / stop function.

The best (safe) practice is to have one person at the top and one person at the bottom, with an effective means of communication between them. Transport one item at a time which will lower the risks of one of the people been overwhelmed. Note: always be in control of the contents on the conveyor. An application specific training document should created and followed at all times, with a copy of it and the relevant safety signs displayed near the conveyor.

Load distribution on incline conveyors

Due to the nature of incline conveyors, care must be taken in the packing of boxes totes and general positioning of items. The load must be as evenly spread against the conveyor belt, for example, do not stand a coat rack up on the conveyor and expect it not to fall over. When using boxes or totes make sure the load is spread out on the bottom of the box (see sketch)




Do not place items directly onto a moving conveyor belt.
Do not load an inclined belt whilst the conveyor is stopped.

An ideal loading involves placing the item on a gravity roller or fixed table and gently pushing the package (from the top of the package) towards the moving belt until the moving belt takes it away.

Position and orientation of items on the belt.

Items should always be placed centrally on the belt with short side leading



General safety.

If the conveyor is to be used by more than one team of people, We would recommend a reporting book, white board etc to pass information team to team

Maintenance checks

OPERATOR

Daily:

Check the general condition of belt. - Report any problems to an engineer
Visually check fixings for loose fixings

ENGINEER

Monthly:

Check condition of drive drum and return rollers, repair or replace as required.
Ensure tracking is correct, adjust if required.
Check fixings are tight

NOTE: Before any work is carried out ensure the equipment is properly secured isolated from the mains.

Conveyor Belt Tracking

1. The basic rule of tracking a conveyor belt - Is the drive roller must be at the out feed end.
2. The conveyor frame, must be straight, lined and levelled.
3. All pulleys and snub rollers must be square to the frame and parallel to each other. (Check by measuring diagonal dimensions
4. The conveyor frame should be checked for obstruction and snagging
5. Belt tension should be applied evenly, until such the belt moves. (Do not keep putting tension in the belt - this will put additional pressure on the drive motor and stretch the belt)
6. Tracking adjustment should be carried out in small intervals. (Time should be given for any adjustment to take effect.

TROUBLESHOOTING "TRACKING"

ALL PORTIONS OF CONVEYOR BELT RUNNING TO ONE SIDE AT A GIVEN POINT ON STRUCTURE.

1. One or more idlers immediately preceding trouble point not at right angles to the direction of belt travel.
2. Advance, in the direction of belt travel, the end of the idler to which the belt has shifted. Square end rollers.
3. Conveyor frame or structure crooked.
Using string line to check and adjust as required
1. Sticking idlers.
2. Clean and lubricate.
3. Belt runs off terminal pulley.
4. Check terminal pulley assignment. Check alignments of return rollers near terminal rollers.
5. Build up of material on idlers.
6. Clean them. Install cleaning device.
7. Structure not level and belt tends to shift to low side.
8. Level structure.

PARTICULAR SECTION OF CONVEYOR BELT RUNS TO ONE SIDE AT ALL POINTS ON CONVEYOR.

- Belt not joined squarely.
 - Square ends/resplice.
- Bowed belt.
 - Tension it or replace.
- CONVEYOR BELT RUNS TO ONE SIDE FOR LONG DISTANCE BED.
 - Load being placed on belt off-center.
 - Adjust chute and loading conditions so as to place load in the center of belt.
 - Conveyor frame or structure crooked.
 - Straighten it.

Manufacturers declaration

According to EC Machinery Directive 2006/42/EC

The manufacturer

Spaceguard Limited

Bergen Way, Hull, UK

Hereby declares that the conveyor module described belt

- Belt conveyor
- Serial numbers between: 17259

Is not a ready to use machine according to the EC machinery directive and therefore does not fully comply with the requirements of this directive.

Initial start up of these conveyor modules is not permitted until conformity of the entire machine / system / process in which they are installed has been declared via the EC machinery directive!

Applied EC directives

Machinery directive 2006/42/EC
Low voltage directive 2006/95/EC
EMC Directive 2004/108/EC

Applied harmonised standards

EB ISO 12100 Pt 1 & Pt2
EN 294 Safety of machinery to prevent danger zones been reached
EN 349 Safety of machinery, minimum distances to avoid crushing
EN 60204-1

A handwritten signature in blue ink, appearing to be "NE" followed by a stylized flourish.

Neil Ellerby
Director

9th May 2015



Declaration of EC Conformity

According to the guidelines of the council for adjustment of the legal stipulations for the member states: 2006/42/EC

The manufacturer

Spaceguard Limited

Bergen Way, Hull, UK

Hereby certify that the conveyor module described belt

- Belt conveyor
- With serial number: 11346 to 19000

Complies with all the relevant provisions of the EC Machinery directive and the national laws and regulations adopting this directive. Any modifications to the machine will render this declaration null and void.

Applied EC directives

Machinery directive 2006/42/EC
Low voltage directive 2014/35/EU
EMC Directive 2004/108/EC

With reference to:

EB ISO 12100 Pt 1 & Pt2
EN 30204-1-2006+A1:2009 Electrical equipment of machines
EN 619: 2002 Continuous handling systems and equipment
EN 294 Safety of machinery to prevent danger zones been reached
EN 349 Safety of machinery, minimum distances to avoid crushing
EN 60204-1

On behalf of Spaceguard limited

A handwritten signature in black ink, consisting of stylized, overlapping letters that appear to be 'A' and 'L'.

Director

NOTE: Customer to incorporate within existing line - Conformity on applicable - customer must re-assess complete line for CE